



| miniconfine 300 | material | voltage (Vac) | watt (W) | ccf (K) | beam angle (°) | lumen (lm) | CRI |
|-----------------|---------------------|---------------|----------|---------|----------------|------------|-----|
| 2001-1179 | stainless steel 316 | 220-240 | 9 | 3000 | 50 | 876 | >90 |
| 2001-1179 | stainless steel 316 | 220-240 | 9 | 4000 | 50 | 972 | >90 |
| 2001-1179 | stainless steel 316 | 220-240 | 9 | 3000 | 25 | 876 | >90 |
| 2001-1179 | stainless steel 316 | 220-240 | 9 | 4000 | 25 | 972 | >90 |
| 2001-1179 | stainless steel 316 | 220-240 | 9 | 3000 | 78 x 47 | 876 | >90 |
| 2001-1179 | stainless steel 316 | 220-240 | 9 | 4000 | 78 x 47 | 972 | >90 |
| 2001-1179 | stainless steel 316 | 220-240 | 9 | 3000 | 12 | 876 | >90 |
| 2001-1179 | stainless steel 316 | 220-240 | 9 | 4000 | 12 | 972 | >90 |
| 2001-1179 | stainless steel 316 | 220-240 | 9 | 3000 | 14 x 47 | 876 | >90 |
| 2001-1179 | stainless steel 316 | 220-240 | 9 | 4000 | 14 x 47 | 972 | >90 |

colors

■ stainless steel

accessories

| | |
|------------|------------------------------------|
| 2001-AC204 | IP 68 fast connector |
| 2001-AC279 | IP 68 connector for through wiring |
| 2001-AC603 | Rough-in housing |