



confine 600	material	voltage (Vac)	watt (W)	ccf (K)	beam angle (°)	lumen (lm)	CRI
2001-1296	stainless steel 316	220-240	18	3000	25	1752	>90
2001-1296	stainless steel 316	220-240	18	4000	25	1944	>90
2001-1296	stainless steel 316	220-240	18	3000	78 x 47	1752	>90
2001-1296	stainless steel 316	220-240	18	4000	78 x 47	1944	>90
2001-1296	stainless steel 316	220-240	25.2	3000	25	2352	>90
2001-1296	stainless steel 316	220-240	25.2	4000	25	2616	>90
2001-1296	stainless steel 316	220-240	25.2	3000	78 x 47	2352	>90
2001-1296	stainless steel 316	220-240	25.2	4000	78 x 47	2616	>90
2001-1296	stainless steel 316	220-240	32	4000	78 x 47	3364	>90
2001-1296	stainless steel 316	220-240	32	3000	25	3024	>90
2001-1296	stainless steel 316	220-240	32	4000	25	3364	>90
2001-1296	stainless steel 316	220-240	32	3000	78 x 47	3024	>90
2001-1296	stainless steel 316	220-240	18	3000	14 x 47	1752	>90
2001-1296	stainless steel 316	220-240	18	4000	14 x 47	1944	>90
2001-1296	stainless steel 316	220-240	25.2	3000	14 x 47	2352	>90
2001-1296	stainless steel 316	220-240	25.2	4000	14 x 47	2616	>90
2001-1296	stainless steel 316	220-240	32	3000	14 x 47	3024	>90
2001-1296	stainless steel 316	220-240	32	4000	14 x 47	3364	>90
2001-1296	stainless steel 316	220-240	18	3000	50	1752	>90
2001-1296	stainless steel 316	220-240	18	4000	50	1944	>90
2001-1296	stainless steel 316	220-240	25.2	3000	50	2352	>90
2001-1296	stainless steel 316	220-240	25.2	4000	50	2616	>90
2001-1296	stainless steel 316	220-240	32	3000	50	3024	>90
2001-1296	stainless steel 316	220-240	32	4000	50	3364	>90
2001-1296	stainless steel 316	220-240	18	3000	12	1752	>90
2001-1296	stainless steel 316	220-240	18	4000	12	1944	>90
2001-1296	stainless steel 316	220-240	25.2	3000	12	2352	>90
2001-1296	stainless steel 316	220-240	25.2	4000	12	2616	>90
2001-1296	stainless steel 316	220-240	32	3000	12	3024	>90
2001-1296	stainless steel 316	220-240	32	4000	12	3364	>90

#### colors

■ stainless steel

#### accessories



2001-AC204	IP 68 fast connector
2001-AC279	IP 68 connector for through wiring
2001-AC281	Rough-in housing 635x140x100