



confine 900	material	voltage (Vac)	watt (W)	cct (K)	beam angle (°)	lumen (lm)	CRI
2001-1297	stainless steel 316	220-240	27	3000	25	2628	>90
2001-1297	stainless steel 316	220-240	27	4000	25	2916	>90
2001-1297	stainless steel 316	220-240	27	3000	78 x 47	2628	>90
2001-1297	stainless steel 316	220-240	27	4000	78 x 47	2916	>90
2001-1297	stainless steel 316	220-240	37,8	3000	25	3528	>90
2001-1297	stainless steel 316	220-240	37,8	4000	25	3924	>90
2001-1297	stainless steel 316	220-240	37,8	3000	78 x 47	3528	>90
2001-1297	stainless steel 316	220-240	37,8	4000	78 x 47	3924	>90
2001-1297	stainless steel 316	220-240	48	4000	78 x 47	5046	>90
2001-1297	stainless steel 316	220-240	48	3000	25	4536	>90
2001-1297	stainless steel 316	220-240	48	4000	25	5046	>90
2001-1297	stainless steel 316	220-240	48	3000	78 x 47	4536	>90
2001-1297	stainless steel 316	220-240	48	4000	12	5046	>90
2001-1297	stainless steel 316	220-240	27	3000	12	2628	>90
2001-1297	stainless steel 316	220-240	27	4000	12	2916	>90
2001-1297	stainless steel 316	220-240	37,8	3000	12	3528	>90
2001-1297	stainless steel 316	220-240	37,8	4000	12	3924	>90
2001-1297	stainless steel 316	220-240	48	3000	12	4536	>90
2001-1297	stainless steel 316	220-240	27	3000	50	2628	>90
2001-1297	stainless steel 316	220-240	27	4000	50	2916	>90
2001-1297	stainless steel 316	220-240	37,8	3000	50	3528	>90
2001-1297	stainless steel 316	220-240	37,8	4000	50	3924	>90
2001-1297	stainless steel 316	220-240	48	3000	50	4536	>90
2001-1297	stainless steel 316	220-240	48	4000	50	5046	>90
2001-1297	stainless steel 316	220-240	27	3000	14 x 47	2628	>90
2001-1297	stainless steel 316	220-240	27	4000	14 x 47	2916	>90
2001-1297	stainless steel 316	220-240	37,8	3000	14 x 47	3528	>90
2001-1297	stainless steel 316	220-240	37,8	4000	14 x 47	3924	>90
2001-1297	stainless steel 316	220-240	48	4000	14 x 47	5046	>90
2001-1297	stainless steel 316	220-240	48	3000	14 x 47	4536	>90

colors

 stainless steel

accessories



2001-AC204	IP 68 fast connector
2001-AC279	IP 68 connector for through wiring
2001-AC282	Rough-in housing 940x140x100