



maxitratto 300	material	voltage (Vdc)	watt (W)	cct (K)	beam angle (°)	lumen (lm)	CRI
2001-1545	extruded aluminum	24	9	3000	78 x 47	876	>90
2001-1545	extruded aluminum	24	9	4000	78 x 47	972	>90
2001-1545	extruded aluminum	24	12,6	3000	14 x 47	1176	>90
2001-1545	extruded aluminum	24	12,6	4000	14 x 47	1308	>90
2001-1545	extruded aluminum	24	12,6	3000	25	1176	>90
2001-1545	extruded aluminum	24	12,6	4000	25	1308	>90
2001-1545	extruded aluminum	24	12,6	3000	78 x 47	1176	>90
2001-1545	extruded aluminum	24	12,6	4000	78 x 47	1308	>90
2001-1545	extruded aluminum	24	12,6	3000	50	1176	>90
2001-1545	extruded aluminum	24	12,6	4000	50	1308	>90
2001-1545	extruded aluminum	24	12,6	3000	12	1176	>90
2001-1545	extruded aluminum	24	12,6	4000	12	1308	>90
2001-1545	extruded aluminum	24	9	4000	12	972	>90
2001-1545	extruded aluminum	24	9	3000	12	876	>90
2001-1545	extruded aluminum	24	9	4000	25	972	>90
2001-1545	extruded aluminum	24	9	3000	25	876	>90
2001-1545	extruded aluminum	24	9	4000	50	972	>90
2001-1545	extruded aluminum	24	9	3000	50	876	>90
2001-1545	extruded aluminum	24	9	4000	14 x 47	972	>90
2001-1545	extruded aluminum	24	9	3000	14 x 47	876	>90
2001-1545	extruded aluminum	24	3,63	3000	69 x 139	433	>90
2001-1545	extruded aluminum	24	3,63	4000	69 x 139	476	>90
2001-1545	extruded aluminum	24	6	3000	69 x 139	642	>90
2001-1545	extruded aluminum	24	6	4000	69 x 139	664	>90

colors

■ .2 black



accessories	
2001-AC205-IP66	IP66 remote power supply box
2001-AC279	IP 68 connector for through wiring
2001-AC433	Rough-in housing Maxitratto 330mm
2001-AC551	Extraction tool Traccia