



maxitratto 600	material	voltage (Vdc)	watt (W)	cct (K)	beam angle (°)	lumen (lm)	CRI
2001-1546	extruded aluminum	24	18	3000	78 x 47	1752	>90
2001-1546	extruded aluminum	24	18	4000	78 x 47	1944	>90
2001-1546	extruded aluminum	24	25,2	3000	14 x 47	2352	>90
2001-1546	extruded aluminum	24	25,2	4000	14 x 47	2616	>90
2001-1546	extruded aluminum	24	25,2	3000	25	2352	>90
2001-1546	extruded aluminum	24	25,2	4000	25	2616	>90
2001-1546	extruded aluminum	24	25,2	3000	78 x 47	2352	>90
2001-1546	extruded aluminum	24	25,2	4000	78 x 47	2616	>90
2001-1546	extruded aluminum	24	25,2	3000	12	2352	>90
2001-1546	extruded aluminum	24	25,2	4000	12	2616	>90
2001-1546	extruded aluminum	24	25,2	3000	50	2352	>90
2001-1546	extruded aluminum	24	25,2	4000	50	2616	>90
2001-1546	extruded aluminum	24	18	3000	14 x 47	1752	>90
2001-1546	extruded aluminum	24	18	4000	14 x 47	1944	>90
2001-1546	extruded aluminum	24	18	3000	50	1752	>90
2001-1546	extruded aluminum	24	18	4000	50	1944	>90
2001-1546	extruded aluminum	24	18	3000	25	1752	>90
2001-1546	extruded aluminum	24	18	4000	25	1944	>90
2001-1546	extruded aluminum	24	18	4000	12	1944	>90
2001-1546	extruded aluminum	24	18	3000	12	1752	>90
2001-1546	extruded aluminum	24	7,98	3000	69 x 139	952	>90
2001-1546	extruded aluminum	24	7,98	4000	69 x 139	1047	>90
2001-1546	extruded aluminum	24	12	3000	69 x 139	1284	>90
2001-1546	extruded aluminum	24	12	4000	69 x 139	1328	>90

colors

■ .2 black



accessories	
2001-AC205-IP66	IP66 remote power supply box
2001-AC279	IP 68 connector for through wiring
2001-AC434	Rough-in housing Maxitratto 600mm
2001-AC551	Extraction tool Traccia