


maxitratto 1200	material	voltage (Vdc)	watt (W)	cct (K)	beam angle (°)	lumen (lm)	CRI
2001-1548	extruded aluminum	24	36	3000	78 x 47	3504	>90
2001-1548	extruded aluminum	24	36	4000	78 x 47	3888	>90
2001-1548	extruded aluminum	24	50,4	3000	14 x 47	4704	>90
2001-1548	extruded aluminum	24	50,4	4000	14 x 47	5232	>90
2001-1548	extruded aluminum	24	50,4	3000	25	4704	>90
2001-1548	extruded aluminum	24	50,4	4000	25	5232	>90
2001-1548	extruded aluminum	24	50,4	3000	78 x 47	4704	>90
2001-1548	extruded aluminum	24	50,4	4000	78 x 47	5232	>90
2001-1548	extruded aluminum	24	50,4	4000	12	5232	>90
2001-1548	extruded aluminum	24	50,4	3000	12	4704	>90
2001-1548	extruded aluminum	24	50,4	4000	50	5232	>90
2001-1548	extruded aluminum	24	50,4	3000	50	4704	>90
2001-1548	extruded aluminum	24	36	3000	14 x 47	3504	>90
2001-1548	extruded aluminum	24	36	3000	50	3504	>90
2001-1548	extruded aluminum	24	36	4000	14 x 47	3888	>90
2001-1548	extruded aluminum	24	36	4000	50	3888	>90
2001-1548	extruded aluminum	24	36	3000	25	3504	>90
2001-1548	extruded aluminum	24	36	4000	25	3888	>90
2001-1548	extruded aluminum	24	36	4000	12	3888	>90
2001-1548	extruded aluminum	24	36	3000	12	3504	>90
2001-1548	extruded aluminum	24	16,68	3000	69 x 139	1990	>90
2001-1548	extruded aluminum	24	16,68	4000	69 x 139	2188	>90
2001-1548	extruded aluminum	24	24	3000	69 x 139	2568	>90
2001-1548	extruded aluminum	24	24	4000	69 x 139	2656	>90

**colors**

■ .2 black



accessories	
2001-AC205-IP66	IP66 remote power supply box
2001-AC279	IP 68 connector for through wiring
2001-AC436	Rough-in housing Maxitratto 1185mm
2001-AC551	Extraction tool Traccia
2001-AC538	Anti glare louver Maxitratto 1200mm